

Product Verification

Sustainability

Product Systems

EGOSILICON 151

EGO Dichtstoffwerke GmbH & Co. Betriebs KG

EGOSILICONE 151 is a ready-to-use, extremely high-quality, abrasion-resistant and plasticiser-free single-component silicone sealant with best processing characteristics that vulcanises through reaction with air humidity to form an elastic end product. EGOSILICONE 151 is resistant to chemicals (diluted acids and lyes, household cleaning agents and the like), fungicidal and waterproof with optimum skinforming time and secure vulcanisation; it ensures excellent processing characteristics and very good modeling and smoothing properties. Permanent high-quality sealing in the fields of construction and sanitary applications. For sealing, edge and connection joints in glass, ceramics, porcelain, enamel, tiles, aluminium, stainless steel, polyacrylate, polycarbonate, polyester, hard PVC and timber. EGOSILICONE 151 fulfills the requirements according to EMICODE EC 1.

<https://www.ego.de/produkt/egosilicon151>



■ Ecolabels & Product-Assessments

AgBB tested



EMICODE EC1



EPD Institut Bauen und Umwelt e.V.



French VOC-Label A+


 ISO 14001 - Environmental
 Management System

 ISO 9001 - Quality
 Management System


SCAQMD 1168



■ Product Properties

Ingredients:

SVHC according REACH < 0,1 %:	Yes
Percentage of the product's composition, that is known to the chemical ingredient level	100 wt%
Free (< 0,1 %) of chlorinated paraffins (= CP inkl. SCCP, MCCP, LCCP):	Yes
Free (< 0,1 %) of biocidal:	No
Free (< 0,1 %) of polybrominated diphenyl ethers (= PBDE):	Yes
Recycled content pre-consumer:	N/A
Recycled content post-consumer:	N/A
Free (< 0,1 %) of hydrocarbon (KWS) plasticizer:	Yes
VOC content according 2004/42/EG:	0 g/l
VOC content according 2004/42/EG:	0 g/m ²
To what level of detail is the product composition known?	100 ppm
Rapidly renewable content	N/A
Non renewable virgin raw material content	N/A
Free (< 0,1 %) of polybrominated biphenyls (= PBB):	Yes
Free (< 0,1 %) of hexabromocyclododecane (= HBCD):	Yes
Free (< 0,1 %) of tris (2-carboxyethyl) phosphine (= TCEP):	Yes
Free (< 0,1 %) of lead:	Yes
Free (< 0,1 %) of cadmium:	Yes
Free (< 0,1 %) of chromium-VI compounds:	Yes

Free of solvent according to VdL-RL01:	Yes
Free (< 0,1 %) of aromatic compounds:	Yes
Free (< 0,1 %) from halogenated propellants:	Yes
Free (< 0,1 %) of halogenated flame retardants:	No
Content of VOC:	0 %
Content of solvents:	0 %
Free (< 0,1 %) of halogens:	Yes
Free of plasticizer according to VdL-RL01:	Yes

Manufacturer:

Environmental Management System according ISO 14001:	Yes
Final manufacturing location of the product: latitude	47.490138178497375 ° DDD
Final manufacturing location of the product: longitude	11.178027746972168 ° DDD

Emissions:

Formaldehyde emissions after 28 days according DIN EN 717-1:	0.002 mg/m ³
R-Value according to AgBB:	0,01
TVOC after 3 days according ISO 16000-3 / AgBB:	0,28 mg/m ³
TVOC after 28 days according ISO 16000-3 / AgBB:	0,038 mg/m ³
Carcinogens 1A and 1B after 3 days according ISO-16000 / AgBB:	0,001 mg/m ³
Carcinogens 1A and 1B after 28 days according ISO-16000 / AgBB:	0,001 mg/m ³
SVOC after 3 days according ISO 16000-3 / AgBB:	N/A
SVOC after 28 days according ISO 16000-3 / AgBB:	N/A

Life Cycle Assessment:

Functional use period	N/A
-----------------------	-----

Circularity:

■ Contact Details Manufacturer

EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Kaltenbrunn 27
82467 Garmisch-Partenkirchen
DE
<http://www.ego.de/>



■ Disclaimer

Notice: This verification is generated by the Assessment Service of BMS. The distribution or publication by third parties is not permitted. The information is based on the manufacturer's specifications. Despite a diligent treatment of all information BMS can not make any warranties about the completeness, reliability and accuracy of this information. The user of the data sheet, the user / purchaser of the product and the consultant / planner, who is advising on this product has the duty to check the product for the intended application at their own responsibility. When a new version of this product verification is produced, the previous version loses its validity.