

# **Product Verification**

# Sustainability

Self declared according to DGNB NBV 2015

Product Systems

### **EGOSILICON 151**

### EGO Dichtstoffwerke GmbH & Co. Betriebs KG

EGOSILICONE 151 is a ready-to-use, extremely high-quality, abrasion-resistant and plasticiser-free single-component silicone sealant with best processing characteristics that vulcanises through reaction with air humidity to form an elastic end product. EGOSILICONE 151 is resistant to chemicals (diluted acids and lyes, household cleaning agents and the like), fungicidal and waterproof with optimum skinforming time and secure vulcanisation; it ensures excellent processing characteristics and very good modeling and smoothing properties. Permanent high-quality sealing in the fields of construction and sanitary applications. For sealing, edge and connection joints in glass, ceramics, porcelain, enamel, tiles, aluminium, stainless steel, polyacrylate, polycarbonate, polyester, hard PVC and timber.

EGOSILICONE 151 fulfills the requirements according to EMICODE EC 1.







# Environmental Quality (ENV) Criteria Product Verification ENV 1.1/2.1 Life cycle assessment (Updated on: 26.01.2017) EPD available: Yes ENV 1.2 Local environmental impact (Updated on: 08.06.2017) Quality level 4 of 4 Legend: yes = Product contributes toward satisfying the credit, N/A = Product not relevant in the credit, no = Credit requirements are not proven

### Summary

### The product contributes to the certification:

- The product has an Environmental Product Declaration (EPD) which can be used to calculate the building life cycle assessment: EPD available: Yes
- Achieved quality level in DGNB Criteria ENV 1.2 Local environmental impact for the entire product: Quality level 4 of 4



### Ecolabels & Product-Assessments

AgBB tested

**EMICODE** 

EMICODE EC1

EPD



EPD Institut Bauen und Umwelt e.V.



ISO 14001 - Environmental Management System



ISO 9001 - Quality Management System





French VOC-Label A+





SCAQMD 1168



### Product Properties

### Ingredients:

SVHC according REACH < 0,1 %: Yes

Percentage of the product's composition, that is known to 100 wt%

the chemical ingredient level

Free (< 0,1 %) of chlorinated paraffins (= CP inkl. SCCP, Yes

MCCP, LCCP):

Free (< 0,1 %) of biocidal:

Free (< 0,1 %) of polybrominated diphenyl ethers (= Yes

PBDE):

Recycled content pre-consumer: N/A

Recycled content post-consumer: N/A

Free (< 0,1 %) of hydrocarbon (KWS) plasticizer: Yes

VOC content according 2004/42/EG: o g/l

VOC content according 2004/42/EG: 0 g/m2

To what level of detail is the product composition known? 100 ppm

Rapidly renewable content N/A

Non renewable virgin raw material content N/A

Free (< 0,1 %) of polybrominated biphenyls (= PBB): Yes



Free (< 0,1 %) of hexabromocyclododecane (= HBCD): Yes Free (< 0,1 %) of tris (2-carboxyethyl) phosphine (= TCEP): Yes Free (< 0,1 %) of lead: Yes Free (< 0,1 %) of cadmium: Yes Free (< 0,1 %) of chromium-VI compounds: Yes Free of solvent according to VdL-RLo1: Yes Free (< 0,1 %) of aromatic compounds: Yes Free (< 0,1 %) from halogenated propellants: Yes Free (< 0,1 %) of halogenated flame retardants: No Content of VOC: 0 % Content of solvents: 0 % Free (< 0,1 %) of halogens: Yes Free of plasticizer according to VdL-RLo1: Yes

### Manufacturer:

Environmental Management System according ISO 14001: Yes

Final manufacturing location of the product: latitude 47.490138178497375 ° DDD Final manufacturing location of the product: longitude 11.178027746972168 ° DDD

### **Emissions:**

Formaldehyde emissions after 28 days according DIN EN  $\,$  0.002 mg/m³  $\,$ 

717-1:

R-Value according to AgBB: 0,01

TVOC after 3 days according ISO 16000-3 / AgBB: 0,28 mg/m³

TVOC after 28 days according ISO 16000-3 / AgBB: 0,038 mg/m<sup>3</sup>

Carcinogens 1A and 1B after 3 days according ISO-16000  $\,$  0,001  $\rm mg/m^3$ 

/ AgBB:

Carcinogens 1A and 1B after 28 days according ISO-16000 0.001 mg/m³

/ AgBB:

SVOC after 3 days according ISO 16000-3 / AgBB: N/A

SVOC after 28 days according ISO 16000-3 / AgBB: N/A

### Life Cycle Assessment:

Functional use period N/A


### Circularity:



### System description

The DGNB certification system was founded by the "German Sustainable Building Council" and first appeared on the market in 2008. The DGNB system evaluates buildings holistically on the basis of individual criteria within the categories Ecological Quality, Economic Quality, Sociocultural and Functional Quality, Technical Quality, Process Quality and Location Quality. Different profiles allow the certification of new buildings and existing buildings, as well as of quarters in Germany and Internationally. Buildings can achieve a certification in Bronze, Silver, Gold and Platinum. Up to now, more than 3,500 projects have been awarded by the DGNB (as of June 2018).

Source: www.dgnb.de





# **Detailed Verification**

Self declared according to DGNB NBV 2015

Environmental Quality (ENV)

ENV 1.1/2.1 Life cycle assessment (Updated on: 26.01.2017)

The product has an Environmental Product Declaration (EPD) which can be used to calculate the building life cycle assessment:

**EGOSILICON 151** EPD available: Yes An environmental product declaration exists for the product: **EGOSILICON 151** Yes EPD Owner of the Declaration: DBC, EFCC, FEICA, IVK **EGOSILICON 151** EPD Publisher: **EGOSILICON 151** Institut Bauen und Umwelt e.V. (IBU) EPD Programme holder: **EGOSILICON 151** Institut Bauen und Umwelt e.V. (IBU) EPD Declaration number: EPD-DBC-20220180-IBF1-EN **EGOSILICON 151** EPD Issue date: EGOSILICON 151 31.08.2022 EPD valid to:

ENV 1.2 Local environmental impact (Updated on: 08.06.2017

Achieved quality level in DGNB Criteria ENV 1.2 Local environmental impact for the entire product:

EGOSILICON 151 Quality level 4 of 4

Achieved quality level in DGNB Criterion ENV 1.2 Local environmental impact:

EGOSILICON 151 Quality level 4

31.05.2027

**EGOSILICON 151** 



Row 12: Adhesions of mechanically stressed joints over small areas; the areas glass construction, façade and fire protection are not considered here. Sealing compounds, sealing substances, adhesives for dot like and linear adhesions of components in the interior area. Acrylate sealing substances/adhesives and silicone sealing substances are what is meant here.

Achieved quality level in DGNB ENV 1.2 Row 12 for the entire product:

EGOSILICON 151	Quality level 4
Achieved quality level in DGNB ENV 1.2 Row 12:	
EGOSILICON 151	Quality level 4
Adhesives and sealants (acrylate, silicone, SMP) - interior and technical building equipments (DGNB ENV1.2 Row 12):	
EGOSILICON 151	Yes
Free of chlorinated paraffins (CP):  EGOSILICON 151	Yes
Content of solvent < 1 %:	
EGOSILICON 151	Yes
Content of solvents:	
EGOSILICON 151	0 %
Free (< 0,1 %) of KWS plasticizers:	
EGOSILICON 151	Yes



### Contact Details Manufacturer

### EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Kaltenbrunn 27 82467 Garmisch-Partenkirchen DE



### Disclaimer

This verification is the evaluation and ranking of products in terms of the certification system DGNB 2015 (New construction of office buildings). The DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen) generally does not certify products. Therefore the project team or the manufacturer is responsible to declare compliance with respect to the DGNB criteria. Notice: This verification is generated by the Assessment Service of BMS. The distribution or publication by third parties is not permitted. The data sheet is not a DGNB certification document. The information is based on the manufacturer's specifications. Despite a diligent treatment of all information BMS can not make any warranties about the completeness, reliability and accuracy of this information. The requirements of DGNB can be interpreted differently and depend on the project and scope of application. Therefore, BMS cannot accept any liability for the evaluation in terms of the DGNB criteria. The user of the data sheet, the user / purchaser of the product and the consultant / planner, who is advising on this product has the duty to check the product for the intended application at their own responsibility. When a new version of this product verification is produced, the previous version loses its validity.