

Product Verification

Sustainability


Product Systems

EGOTAPE 1000

EGO Dichtstoffwerke GmbH & Co. Betriebs KG

EGOTAPE 1000 is a self-adhesive and malleable butyl sealant tape that is stable in volume. The product is laminated with a highly flexible and transparent PE-film that can be two-dimensionally elongated to up to 300%. The film is primarily intended for application of the tape, sealing is ensured by the butyl. The product corresponds to the requirements of the IVD leaflet no. 5. Long-lasting adhesion, ageing and weather resistance as well as the typical butyl characteristics, such as UV resistance, longevity and odourlessness, make EGOTAPE 1000 and EGOTAPE 2000 stand out for butyl rubber products. EGOTAPE 1000 fulfills the requirements according to EMICODE EC 1 PLUS.

<https://www.ego.de/produkt/egotape1000>



Ecolabels & Product-Assessments

AgBB tested



ISO 9001 - Quality
Management System



EMICODE EC1plus



French VOC-Label A+



ISO 14001 - Environmental
Management System



Product Properties

Ingredients:

| | |
|---|---------|
| Percentage of the product's composition, that is known to the chemical ingredient level | 100 wt% |
| SVHC according REACH < 0,1 %: | Yes |
| VOC content according 2004/42/EG: | 0 g/l |
| VOC content according 2004/42/EG: | 0 g/m2 |
| Recycled content pre-consumer: | N/A |
| Recycled content post-consumer: | N/A |
| To what level of detail is the product composition known? | 100 ppm |
| Rapidly renewable content | N/A |
| Non renewable virgin raw material content | N/A |
| Free (< 0,1 %) of biocidal: | Yes |
| Free (< 0,1 %) of chlorinated paraffins (= CP inkl. SCCP, MCCP, LCCP): | Yes |
| Free (< 0,1 %) of polybrominated diphenyl ethers (= PBDE): | Yes |
| Free (< 0,1 %) of polybrominated biphenyls (= PBB): | Yes |
| Free (< 0,1 %) of hexabromocyclododecane (= HBCD): | Yes |
| Free (< 0,1 %) of tris (2-carboxyethyl) phosphine (= TCEP): | Yes |
| Free (< 0,1 %) of lead: | Yes |
| Free (< 0,1 %) of cadmium: | Yes |
| Free (< 0,1 %) of chromium-VI compounds: | Yes |

| | |
|--|-----|
| Free of solvent according to VdL-RL01: | Yes |
| Free (< 0,1 %) of aromatic compounds: | Yes |
| Free (< 0,1 %) from halogenated propellants: | Yes |
| Free (< 0,1 %) of tin: | Yes |
| Free (< 0,1 %) of halogenated flame retardants: | Yes |
| Content of solvents: | 0 % |
| Content of VOC: | 0 % |
| Free (< 0,1 %) of halogens: | Yes |
| Free of plasticizer according to VdL-RL01: | Yes |
| Free (< 0,1 %) of hydrocarbon (KWS) plasticizer: | Yes |

Manufacturer:

| | |
|--|--------------------------|
| Environmental Management System according ISO 14001: | Yes |
| Final manufacturing location of the product: latitude | 47.49021067502303 ° DDD |
| Final manufacturing location of the product: longitude | 11.178312060958389 ° DDD |

Emissions:

| | |
|---|-------------------------|
| Formaldehyde emissions after 28 days according DIN EN 717-1: | 0.002 mg/m ³ |
| R-Value according to AgBB: | 0,0 |
| TVOC after 3 days according ISO 16000-3 / AgBB: | 0,02 mg/m ³ |
| TVOC after 28 days according ISO 16000-3 / AgBB: | 0,005 mg/m ³ |
| SVOC after 3 days according ISO 16000-3 / AgBB: | N/A |
| SVOC after 28 days according ISO 16000-3 / AgBB: | N/A |
| Carcinogens 1A and 1B after 3 days according ISO-16000 / AgBB: | 0,001 mg/m ³ |
| Carcinogens 1A and 1B after 28 days according ISO-16000 / AgBB: | 0.001 mg/m ³ |

Life Cycle Assessment:

| | |
|-----------------------|-----|
| Functional use period | N/A |
|-----------------------|-----|

Circularity:

| | |
|--|----|
| Has the product been designed for reuse, refurbishment or remanufacturing? | No |
| Is the product designed for a recycling of equal quality? | No |
| Was the product designed for clean incineration? | No |

Was the Product designed for emission or direct dispersal? No

Was the product designed for biodegradation? No

■ Contact Details Manufacturer

EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Kaltenbrunn 27
82467 Garmisch-Partenkirchen
DE
<http://www.ego.de/>



■ Disclaimer

Notice: This verification is generated by the Assessment Service of BMS. The distribution or publication by third parties is not permitted. The information is based on the manufacturer's specifications. Despite a diligent treatment of all information BMS can not make any warranties about the completeness, reliability and accuracy of this information. The user of the data sheet, the user / purchaser of the product and the consultant / planner, who is advising on this product has the duty to check the product for the intended application at their own responsibility. When a new version of this product verification is produced, the previous version loses its validity.