

# Product Verification

## Sustainability

Self declared according to DGNB Neubau 2018


### Product Systems

#### EGOTAPE 1000

EGO Dichtstoffwerke GmbH & Co. Betriebs KG

EGOTAPE 1000 is a self-adhesive and malleable butyl sealant tape that is stable in volume. The product is laminated with a highly flexible and transparent PE-film that can be two-dimensionally elongated to up to 300%. The film is primarily intended for application of the tape, sealing is ensured by the butyl. The product corresponds to the requirements of the IVD leaflet no. 5. Long-lasting adhesion, ageing and weather resistance as well as the typical butyl characteristics, such as UV resistance, longevity and odourlessness, make EGOTAPE 1000 and EGOTAPE 2000 stand out for butyl rubber products. EGOTAPE 1000 fulfills the requirements according to EMICODE EC 1 PLUS.

<https://www.ego.de/produkt/egotape1000>



## ■ Product Assessment

### Environmental Quality (ENV)

#### Criteria

#### Product Verification

ENV 1.2 Local environmental impact (Updated on: 05.01.2022)

Quality level 4 of 4

Legend: yes = Product contributes toward satisfying the credit, N/A = Product not relevant in the credit, no = Credit requirements are not proven

## ■ Summary

### The product contributes to the certification:

- Achieved quality level in DGNB 2018 Criteria ENV 1.2 Local environmental impact for the entire product: Quality level 4 of 4

## Ecolabels & Product-Assessments

AgBB tested



ISO 9001 - Quality  
Management System



EMICODE EC1plus



French VOC-Label A+



ISO 14001 - Environmental  
Management System



## Product Properties

### Ingredients:

Percentage of the product's composition, that is known to the chemical ingredient level	100 wt%
SVHC according REACH < 0,1 %:	Yes
VOC content according 2004/42/EG:	0 g/l
VOC content according 2004/42/EG:	0 g/m2
Recycled content pre-consumer:	N/A
Recycled content post-consumer:	N/A
To what level of detail is the product composition known?	100 ppm
Rapidly renewable content	N/A
Non renewable virgin raw material content	N/A
Free (< 0,1 %) of biocidal:	Yes
Free (< 0,1 %) of chlorinated paraffins (= CP inkl. SCCP, MCCP, LCCP):	Yes
Free (< 0,1 %) of polybrominated diphenyl ethers (= PBDE):	Yes
Free (< 0,1 %) of polybrominated biphenyls (= PBB):	Yes
Free (< 0,1 %) of hexabromocyclododecane (= HBCD):	Yes
Free (< 0,1 %) of tris (2-carboxyethyl) phosphine (= TCEP):	Yes
Free (< 0,1 %) of lead:	Yes
Free (< 0,1 %) of cadmium:	Yes
Free (< 0,1 %) of chromium-VI compounds:	Yes

Free of solvent according to VdL-RL01:	Yes
Free (< 0,1 %) of aromatic compounds:	Yes
Free (< 0,1 %) from halogenated propellants:	Yes
Free (< 0,1 %) of tin:	Yes
Free (< 0,1 %) of halogenated flame retardants:	Yes
Content of solvents:	0 %
Content of VOC:	0 %
Free (< 0,1 %) of halogens:	Yes
Free of plasticizer according to VdL-RL01:	Yes
Free (< 0,1 %) of hydrocarbon (KWS) plasticizer:	Yes

### Manufacturer:

Environmental Management System according ISO 14001:	Yes
Final manufacturing location of the product: latitude	47.49021067502303 ° DDD
Final manufacturing location of the product: longitude	11.178312060958389 ° DDD

### Emissions:

Formaldehyde emissions after 28 days according DIN EN 717-1:	0.002 mg/m <sup>3</sup>
R-Value according to AgBB:	0,0
TVOC after 3 days according ISO 16000-3 / AgBB:	0,02 mg/m <sup>3</sup>
TVOC after 28 days according ISO 16000-3 / AgBB:	0,005 mg/m <sup>3</sup>
SVOC after 3 days according ISO 16000-3 / AgBB:	N/A
SVOC after 28 days according ISO 16000-3 / AgBB:	N/A
Carcinogens 1A and 1B after 3 days according ISO-16000 / AgBB:	0,001 mg/m <sup>3</sup>
Carcinogens 1A and 1B after 28 days according ISO-16000 / AgBB:	0.001 mg/m <sup>3</sup>

### Life Cycle Assessment:

Functional use period	N/A
-----------------------	-----

### Circularity:

Has the product been designed for reuse, refurbishment or remanufacturing?	No
Is the product designed for a recycling of equal quality?	No
Was the product designed for clean incineration?	No

Was the Product designed for emission or direct dispersal? No

Was the product designed for biodegradation? No


## System description

The DGNB certification system was founded by the "German Sustainable Building Council" and first appeared on the market in 2008. The DGNB system evaluates buildings holistically on the basis of individual criteria within the categories Ecological Quality, Economic Quality, Sociocultural and Functional Quality, Technical Quality, Process Quality and Location Quality. Different profiles allow the certification of new buildings and existing buildings, as well as of quarters in Germany and Internationally. Buildings can achieve a certification in Bronze, Silver, Gold and Platinum. Up to now, more than 3,500 projects have been awarded by the DGNB (as of June 2018).

Source: [www.dgnb.de](http://www.dgnb.de)

## System categories

### Category Weighting



Source: DGNB 2018

### Category

### Category considered in product verification

Environmental quality (ENV)	Yes
Economic quality (ECO)	No
Sociocultural and functional quality (SOC)	No
Technical quality (TEC)	No
Process quality (PRO)	Yes
Site quality (SITE)	No

# Detailed Verification

Self declared according to DGNB Neubau 2018

## ■ Environmental Quality (ENV)

### ■ ENV 1.2 Local environmental impact (Updated on: 05.01.2022)

Achieved quality level in DGNB 2018 Criteria ENV 1.2 Local environmental impact for the entire product:

EGOTAPE 1000	Quality level 4 of 4
--------------	----------------------

Achieved quality level in DGNB 2018 Criterion ENV 1.2 Local environmental impact:

EGOTAPE 1000	Quality level 4
--------------	-----------------

Row 13: Assembly adhesives and sealants on the facade, windows and exterior doors (provided by the customer). - Adhesive for the production of airtightness on the facade inside and outside: e.g. PU, PU hybrid, MS polymer, SMP or similar.

Achieved quality level in DGNB 2018 ENV 1.2 Row 13 for the entire product:

EGOTAPE 1000	Quality level 4
--------------	-----------------

Achieved quality level in DGNB 2018 ENV 1.2 Row 13:

EGOTAPE 1000	Quality level 4
--------------	-----------------

Adhesives and sealants (PU, PU hybrid, MS polymer, SMP or the like) - on the façade, windows and external doors (DGNB ENV1.2 Row 13):

EGOTAPE 1000	Yes
--------------	-----

Free of chlorinated paraffins (CP):

EGOTAPE 1000	Yes
--------------	-----

Content of VOC < 1 %:

EGOTAPE 1000	Yes
--------------	-----

Content of VOC:

EGOTAPE 1000	0 %
--------------	-----

Content of halogenated propellants < 0,1 %:

EGOTAPE 1000	Yes
--------------	-----

Certified with EMICODE EC1/EC1PLUS, EC1-R/EC1PLUS-R:

EGOTAPE 1000	Yes
--------------	-----

Certified EMICODE standard:

EGOTAPE 1000	EMICODE EC1PLUS
--------------	-----------------

Certified with Indoor Air Comfort Gold:

EGOTAPE 1000	No
--------------	----

#### ■ Contact Details Manufacturer

##### EGO Dichtstoffwerke GmbH & Co. Betriebs KG

Kaltenbrunn 27  
82467 Garmisch-Partenkirchen  
DE  
<http://www.ego.de/>



#### ■ Disclaimer

This verification is the evaluation and ranking of products in terms of the certification system DGNB 2018 (New construction building). The DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen) generally does not certify products. Therefore the project team or the manufacturer is responsible to declare compliance with respect to the DGNB criteria. Notice: This verification is generated by the Assessment Service of BMS. The distribution or publication by third parties is not permitted. The data sheet is not a DGNB certification document. The information is based on the manufacturer's specifications. Despite a diligent treatment of all information BMS can not make any warranties about the completeness, reliability and accuracy of this information. The requirements of DGNB can be interpreted differently and depend on the project and scope of application. Therefore, BMS cannot accept any liability for the evaluation in terms of the DGNB criteria. The user of the data sheet, the user / purchaser of the product and the consultant / planner, who is advising on this product has the duty to check the product for the intended application at their own responsibility. When a new version of this product verification is produced, the previous version loses its validity.