

## EGOFÜLL PUR HINTERFÜLL

is an open-cell, plasticiser-free, compressible polyurethane foam rod.

### APPLICATION AREAS

Backing of internal connecting and construction joints. Not suited for joints in the building construction according to DIN 18540.

### APPLICATION NOTES

Select a diameter that ensures that the rod is compressed by at least 25 % when installed in the joint. The product does not meet the requirements of DIN 18540.

EGOFÜLL PUR is compatible with all EGO sealants.

### TECHNICAL DATA

Properties	Result	in accordance with
Material basis	Open-cell polyurethane	
Density	18 ± 2kg/m <sup>3</sup>	DIN 53420 ISO EN 845
Compression Hardness	6.0 ± 2,0kPa at 40 % deformation	DIN 53577
Tensile Strength	> 80 kPa	DIN EN 1798
Elongation at Break	> 30 %	DIN EN ISO 1798
Deformation under Pressure	< 50 %	DIN 53572 ISO EN 1856
Tear Resistance	> 0,3 N/mm	DIN 4102

### AVAILABILITY AND STORAGE

Standard Colour	grey, yellow		
Dimension/Packaging	Diametre	Packaging	Metres/Box
	10 mm	1 m rods	1500 m
	15 mm	1 m rods	1000 m
	20 mm	1 m rods	500 m
	25 mm	1 m rods	350 m
	30 mm	1 m rods	250 m
	40 mm	1 m rods	150 m
	50 mm	1 m rods	100 m
Storage	Store in cool and dry conditions		

### SAFETY INSTRUCTIONS

Meets Requirements of	REACH Regulation (EC) No. 1907/2006
Not hazardous	According to EC No. 1272/2008 (CLP)
Not subject to Labelling	According to EC No. 1272/2008 (CLP)
Safety Guidelines	See EC safety data sheet
Disposal	See EC safety data sheet

For warnings refer to the Safety Data Sheet. The above information is the result of thorough research; previous information is hereby invalidated. Check for yourself whether the product is suitable for your purposes. Our possible liability is limited to the value of our product as such. We cannot accept any liability for indirect damage, in particular for the application or unusability of the product. No one is authorized to make recommendations or assurances on our behalf that go beyond the content of our information sheets.