

## EGO LEINÖLKITT ORIGINAL

is a guaranteed pure linseed oil putty, made of linseed oil of the highest quality, using own Upper Bavarian mountain chalk from Kaltenbrunn (Garmisch-Partenkirchen), which has proven itself for decades in the putty industry at home and abroad excellent. It is manufactured according to the quality conditions of RAL 849 / B4 from May 1960.

### APPLICATION AREAS

EGO LEINÖLKITT is suitable for single glazing in timber and metal windows and their combinations for group 1 of RoTa chart (determination of stress groups for glazing windows) worked out by the Institut für Fenstertechnik e. V., Rosenheim or of DIN 18545.

#### Areas of application:

Single glazing

#### Good adhesion to:

wood · metal

### APPLICATION NOTES

- ① Apply EGO Linseed Oil Putty only onto dry and clean profiles that are free from substances liable to impair adhesion.
- ② Timber frames (moisture max. 15 %) must be painted prior to the application.
- ③ Apply EGO Linseed Oil Putty in sufficient quantity and without bubbles.

### STANDARDS AND TESTS

EGO LEINÖLKITT complies with the:

#### Standards:

- DIN 18361 [Glazing work]
- DIN 18545 [Sealing of glazing with sealants]
- DIN 18363 [Paintwork]
- ÖNORM B3722 [Glass in building – Requirements for sealings of glazing rebates and glazing systems with sealants]

#### Technical directives for window paints:

- Instructions 18 by Bundesausschuss Farbe and Sachwertschutz
- In case of profiles made of galvanised steel, non-ferrous metal and marble please contact us.

### TECHNICAL DATA

Properties	Result
Density	approx. 2 g/cm <sup>3</sup>
Application Temperature	+5 °C to approx. +30 °C
Service Temperature	approx. -30 °C to approx. +80 °C
Consistency	softplastic
Properties	hardening, non-shrinking
Method of Application	manually or with EGOFIX Compressed Air Gun
Rework	with polished putty knife, clear smoothing
Secondary Treatment	Smooth carefully with a polished putty knife Overpaint all putty surface with a weather-proof paint at the earliest after skin formation, at the latest after 8 weeks.

### AVAILABILITY AND STORAGE

Standard Colour	grey
Packaging	<ul style="list-style-type: none"> <li>▪ 1 kg bag</li> <li>▪ 5 kg plastic bucket</li> <li>▪ 10 kg plastic bucket</li> <li>▪ 25 kg plastic bucket</li> <li>▪ 25 kg tin bucket</li> </ul>
Storage	Store in original packaging in a cool, dry place: <ul style="list-style-type: none"> <li>▪ 12 months</li> </ul>

## SAFETY INSTRUCTIONS

Meets Requirements of	REACH Regulation (EC) No. 1907/2006
Not hazardous	According to EC No. 1272/2008 (CLP)
Not subject to Labelling	According to EC No. 1272/2008 (CLP)
Safety Guidelines	See EC safety data sheet
Disposal	See EC safety data sheet

For warnings refer to the Safety Data Sheet. The above information is the result of thorough research; previous information is hereby invalidated. Check for yourself whether the product is suitable for your purposes. Our possible liability is limited to the value of our product as such. We cannot accept any liability for indirect damage, in particular for the application or unusability of the product. No one is authorized to make recommendations or assurances on our behalf that go beyond the content of our information sheets.